

Nylon or Vinyl Insulated

Most standard bulk catalog numbers can be put on Mylar Tape for reel fed applications (i.e. 12050 tool and application dies). See pages 190-191. Please put the suffix M for Mylar Tape RA2573M. (Bulk number 1000 and 500 packages.)

Material: copper .050 thk.
 Finish: electro tin-plate
 Wire Range: #16-14
 Color Code: green vinyl or nylon insulator

Nylon #16-14 AWG – Heavy Duty

Cat. No.	Pkg. Qty.	Wire Range	Max. Ins.	Bolt Hole	Wt./Lbs. Per 1000	Dimensions			
						A	B	C	M
RBC14-6	50	16-14 heavy duty	.210	#6	—	.98	.25	.29	.85
RBC853	500	use RC tooling	.210	#6	—	.98	.25	.29	.85
RBC14-8	50	16-14 heavy duty	.210	#8	—	1.04	.39	.29	.85
RBC863	500	use RC tooling	.210	#8	—	1.04	.39	.29	.85
RBC14-10	50	16-14 heavy duty	.210	#10	—	1.04	.39	.29	.85
RBC873	500	use RC tooling	.210	#10	—	1.04	.39	.29	.85
RBC14-14	50	16-14 heavy duty	.210	1/4	—	1.10	.51	.29	.85
RBC713	500	use RC tooling	.210	1/4	—	1.10	.51	.29	.85
RBC14-516	50	16-14 heavy duty	.210	5/16	—	1.21	.54	.38	.94
RBC723	500	use RC tooling	.210	5/16	—	1.21	.54	.38	.94
RBC14-38	50	16-14 heavy duty	.210	3/8	—	1.26	.63	.38	.94
RBC793	500	use RC tooling	.210	3/8	—	1.26	.63	.38	.94
RBC14-12	50	16-14 heavy duty	.210	1/2	—	1.49	.76	.54	1.11
RBC753	500	use RC tooling	.210	1/2	—	1.49	.76	.54	1.11

ERG-2001, WT2000, WT145C, and power tools as recommended crimp in the 12-10 nest (yellow)


Vinyl #16-14 AWG – Heavy Duty

Cat. No.	Pkg. Qty.	Wire Range	Max. Ins.	Bolt Hole	Wt./Lbs. Per 1000	Dimensions			
						A	B	C	M
14RBC-6	50	16-14 heavy duty	.210	#6	5	1.06	.25	.29	.93
RBC857	500	use RC tooling	.210	#6	5	1.06	.25	.29	.93
14RBC-8	50	16-14 heavy duty	.210	#8	5	1.13	.39	.29	.93
RBC867	500	use RC tooling	.210	#8	5	1.13	.39	.29	.93
14RBC-10	50	16-14 heavy duty	.210	#10	5	1.13	.39	.29	.93
RBC877	500	use RC tooling	.210	#10	5	1.13	.39	.29	.93
14RBC-14	50	16-14 heavy duty	.210	1/4"	6	1.19	.51	.29	.93
RBC717	500	use RC tooling	.210	1/4"	6	1.19	.51	.29	.93
14RBC-516	50	16-14 heavy duty	.210	5/16"	6	1.29	.54	.38	1.03
RBC727	500	use RC tooling	.210	5/16"	6	1.29	.54	.38	1.03
14RBC-38	50	16-14 heavy duty	.210	3/8"	6	1.34	.63	.38	1.03
RBC797	500	use RC tooling	.210	3/8"	6	1.34	.63	.38	1.03
14RBC-12	50	16-14 heavy duty	.210	1/2"	6	1.57	.76	.54	1.19
RBC757	500	use RC tooling	.210	1/2"	6	1.57	.76	.54	1.19

Non-Insulated #16-14 AWG – Heavy Duty

Cat. No.	Pkg. Qty.	Wire Range	Max. Ins.	Bolt Hole	Wt./Lbs. Per 1000	Dimensions			
						A	B	C	M
BC14-6	100	16-14 heavy duty	—	#6	—	.81	.25	.29	.68
BC85	500	use RC tooling	—	#6	—	.81	.25	.29	.68
BC14-8	100	16-14 heavy duty	—	#8	—	.87	.39	.29	.68
BC86	500	use RC tooling	—	#8	—	.87	.39	.29	.68
BC14-10	100	16-14 heavy duty	—	#10	—	.87	.39	.29	.68
BC87	500	use RC tooling	—	#10	—	.87	.39	.29	.68
BC14-14	100	16-14 heavy duty	—	1/4	—	.93	.51	.29	.68
BC71	500	use RC tooling	—	1/4"	—	.93	.51	.29	.68
BC14-516	100	16-14 heavy duty	—	5/16	—	1.04	.54	.38	.77
BC72	500	use RC tooling	—	5/16"	—	1.04	.54	.38	.77
BC14-38	100	16-14 heavy duty	—	3/8	—	1.09	.63	.38	.77
BC79	500	use RC tooling	—	3/8"	—	1.09	.63	.38	.77
BC14-12	100	16-14 heavy duty	—	1/2	—	1.32	.76	.54	.94
BC75	500	use RC tooling	—	1/2"	—	1.32	.76	.54	.94

ERG-2002, WT111M, WT2000, and power tools as recommended, crimp in the 12-10 nest



Non-Insulated

Sta-Kon® Terminals



For easily installed, permanent terminations of solid, round, or stranded nichrome wires as used in toasters, irons, heaters, etc. High temperature non-insulated ring terminals and splices are designed for use with solid or stranded resistance wires as used in appliances such as toasters, irons, and heaters.

Stock Thickness:
24-22 ga. = .032
20-18 ga. = .032
16-14 ga. = .040
12-10 ga. = .040

High Temperature Non-Insulated Ring – 1200°F Max.

Terminals for nichrome wire NW Series

Cat. No.	Pkg. Qty.	Wire Range	Bolt Hole	Wt./Lbs. Per 1000	Dimensions			
					A	B	C	M
NW21	1000	24-22	#6	1.5	.59	.31	.28	.44
NW22	1000	24-22	#8	1.5	.59	.31	.28	.44
NW23	1000	24-22	#10	1.5	.59	.31	.28	.44
NW18-10	100	20-18	#10	2.5	.63	.31	.28	.38
NW52	1000	20-18	#8	2.5	.63	.31	.28	.38
NW81	1000	16-14	#6	2.5	.66	.31	.28	.51
NW14-8	100	16-14	#8	2.5	.66	.31	.28	.51
NW14-10	100	16-14	#10	2.5	.66	.31	.28	.51
NW83	1000	16-14	#10	2.5	.66	.31	.28	.51
NW14-12	100	16-14	#12*	2.5	.66	.31	.28	.51
NW84	1000	16-14	#12*	2.5	.66	.31	.28	.51
NW10-8	50	12-10	#8	3	.66	.31	.28	.51
NW10-10	50	12-10	#10	3	.66	.31	.28	.51
NW10-12	50	12-10	#12*	3	.66	.31	.28	.51

* #12 stud is approximate 1/4" stud.

Installing tool: WT1377

Note: Not available on Mylar Tape.

