




**SOD-723 Plastic-Encapsulate Diodes**

**1SS400G** High Speed SWITCHING Diodes

**FEATURES**

- Small surface mounting type
- High Speed
- High reliability with high surge current handing capability



**Maximum Ratings and Electrical Characteristics, Single Diode @T<sub>A</sub>=25°C**

Parameter	Symbol	Limits	Unit
Peak reverse voltage	V <sub>RM</sub>	90	V
DC reverse voltage	V <sub>R</sub>	80	V
Peak forward current	I <sub>FM</sub>	225	mA
Mean rectifying current	I <sub>o</sub>	100	mA
Surge current (1s)	I <sub>surge</sub>	500	mA
Junction temperature	T <sub>j</sub>	125	°C
Storage temperature	T <sub>stg</sub>	-55~+125	°C

**Electrical Ratings @T<sub>A</sub>=25°C**

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Forward voltage	V <sub>F</sub>			1.2	V	I <sub>F</sub> =100mA
Reverse current	I <sub>R</sub>			0.1	μ A	V <sub>R</sub> =80V
Capacitance between terminals	C <sub>T</sub>			3.0	pF	V <sub>R</sub> =0.5V,f=1MHZ
Reverse recovery time	t <sub>rr</sub>			4	ns	V <sub>R</sub> =6V,I <sub>F</sub> =10mA,R <sub>L</sub> =100Ω