


3M™ Round Conductor Flat Cable

.050" 26 AWG Solid, PVC

3306 Series



- 26 AWG wire allows for higher power levels
- Solid wire results in lower cost
- .050 inch centers permit mass termination to a broad line of IDC connectors
- Zippable for branching or discrete termination
- RoHS* Compliant

Date Modified: January 12, 2005

TS-0066-13
Sheet 1 of 2

Physical

Insulation

Material: Polyvinyl Chloride (PVC)

Color: Gray

Marking:

Standard: None

Canadian Option: **AWM 2651 105C 300V VW1** 3M NU

C AWM IA 105C 300V FT1
EU <50V

Conductors: 26 AWG [0.404] Bare Solid Copper

Electrical

Voltage Rating: USA: 300V

Canada: 300V

EU: <50V

Insulation Resistance: $>1 \times 10^{10} \Omega / 10\text{ft [3m]}$

Unbalanced

Balanced

Characteristic Impedance: 103 Ω

171 Ω

Capacitance: 13.6 pF/ft (44.62 pF/m)

7.9 pF/ft (25.91 pF/m)

Inductance: 15 $\mu\text{H/ft}$ (0.49 $\mu\text{H/m}$)

.23 $\mu\text{H/ft}$ (0.75 $\mu\text{H/m}$)

Propagation Delay: 1.40 ns/ft (4.59 ns/m)

1.35 ns/ft (4.43 ns/m)

Velocity of Propagation: 73%

75%

Note: Unbalanced is measured between ground-signal-ground conductors. Balanced is measured between signal conductors within a pair.

Environmental

Temperature Rating: -20°C to +105°C

Flammability Rating: USA: VW-1

Canada: FT1

UL File No.: E42769, Style No.: 2651

RoHS = Directive 2002/95/EC,
Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment



Interconnect Solutions

<http://www.3M.com/interconnects/>

3M is a trademark of 3M Company.

For technical, sales or ordering information call

800-225-5373


3M™ Round Conductor Flat Cable

.050" 26 AWG Solid, PVC

3306 Series



| Number of Conductors | 3M Part Number | Dimension A | Dimension B |
|----------------------|----------------|------------------------|------------------------|
| 10 | 3306/10 | 0.500 ± .010 [12.70] | 0.450 ± .007 [11.43] |
| 14 | 3306/14 | 0.700 ± .010 [17.78] | 0.650 ± .007 [16.51] |
| 16 | 3306/16 | 0.800 ± .015 [20.32] | 0.750 ± .011 [19.05] |
| 20 | 3306/20 | 1.000 ± .015 [25.40] | 0.950 ± .011 [24.13] |
| 24 | 3306/24 | 1.200 ± .015 [30.48] | 1.150 ± .011 [29.21] |
| 26 | 3306/26 | 1.300 ± .015 [33.02] | 1.250 ± .011 [31.75] |
| 34 | 3306/34 | 1.700 ± .020 [43.18] | 1.650 ± .015 [41.91] |
| 40 | 3306/40 | 2.000 ± .020 [50.80] | 1.950 ± .015 [49.53] |
| 50 | 3306/50 | 2.500 ± .020 [63.50] | 2.450 ± .015 [62.23] |
| 60 | 3306/60 | 3.000 ± .020 [76.20] | 2.950 ± .015 [74.93] |



Inch
[mm]

| Tolerance Unless Noted | | | |
|------------------------|-----|------|-------|
| | .0 | .00 | .000 |
| inch | ±.1 | ±.01 | ±.005 |

[] Dimensions for Reference Only

Note: Red marking on one edge of cable designates wire #1.

Ordering Information

3306/XX

Blank = Standard _____
 C = Canadian Certified Version _____

Number of Conductors
(See Table)

Note: Available in standard lengths of 100 feet or 300 feet per roll, please specify when ordering.

TS-0066-13
Sheet 2 of 2

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of 1 year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**

3M

Electronic Solutions Division

6801 River Place Blvd.
Austin, TX 78726-9000
www.3M.com/esd



Minimum 10%
Post-consumer Fiber

Printed in USA.

© 3M 2005