

Detailed information for: AF26-40-00-13

This page contains technical data sheet, documents library and links to offering related to this product. If you require any other information, please contact us using form located at the bottom of the page.

[Print...](#)
[Print to Pdf...](#)

Data Sheet Documentation

AF26-40-00-13

General Information

Extended Product Type:	AF26-40-00-13
Product ID:	1SBL237201R1300
EAN:	3471523115231
Catalog Description:	AF26-40-00-13 100-250V50/60HZ-DC Contactor

Long Description: AF26 4-pole contactors are used for controlling power circuits up to 690 V AC and 440 V DC. They are mainly used for controlling non-inductive or slightly inductive loads (i.e. resistance furnaces...). AF... contactors include an electronic coil interface accepting a wide control voltage $U_c \text{ min. ... } U_c \text{ max.}$ Only four coils cover control voltages between 24...500 V 50/60 Hz or 20...500 V DC. AF contactors can manage large control voltage variations. One coil can be used for different control voltages used worldwide without any coil change. AF contactors have built-in surge protection and do not require additional surge suppressors. The AF... series 4-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 4 N.O. main poles, front and side-mounted add-on auxiliary contact blocks (mechanically-linked auxiliary contacts compliant with Annex L of IEC 60947-5-1. N.C. mirror contacts compliant with Annex F of IEC 60947-4-1) - Control circuit: AC or DC operated - Accessories: a wide range of accessories is available.



Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Across the Line Contactors

Ordering

Minimum Order Quantity:	1 piece
Customs Tariff Number:	85364900

Popular Downloads

Data Sheet, Technical Information:	1SBC101423D0201
Instructions and Manuals:	1SBC101027M6801

Dimensions

Product Net Width:	45 mm
Product Net Depth / Length:	101 mm

Product Net Height:	86 mm
Product Net Weight:	0.360 kg
Technical	
Number of Main Contacts NO:	4
Number of Main Contacts NC:	0
Number of Auxiliary Contacts NO:	0
Number of Auxiliary Contacts NC:	0
Standards:	IEC 60947-1 / 60947-4-1 and EN 60947-1 / 60947-4-1, UL 508, CSA C22.2 N°14
Rated Operational Voltage:	Main Circuit 690 V
Rated Frequency (f):	Main Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I_{th}):	acc. to IEC 60947-4-1, Open Contactors $q = 40\text{ °C } 55\text{ A}$
Rated Operational Current AC-1 (I_e):	(690 V) 40 °C 45 A (690 V) 60 °C 40 A (690 V) 70 °C 32 A
Rated Operational Current AC-3 (I_e):	(220 / 230 / 240 V) 60 °C 23.2 A (380 / 400 V) 60 °C 22 A (415 V) 60 °C 21.2 A (440 V) 60 °C 20 A (500 V) 60 °C 17.6 A (690 V) 60 °C 10.5 A
Rated Operational Power AC-3 (P_e):	(220 / 230 / 240 V) 5.5 kW (400 V) 11 kW (415 V) 11 kW (440 V) 11 kW (500 V) 11 kW (690 V) 9 kW
Rated Short-time Withstand Current (I_{cw}):	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 300 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 55 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 150 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 450 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 225 A for 1 s -empty- A
Maximum Electrical Switching Frequency:	AC-1 600 cycles per hour
Rated Insulation Voltage (U_i):	acc. to UL/CSA 600 V acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 690 V
Rated Impulse Withstand Voltage (U_{imp}):	6 kV
Maximum Mechanical Switching Frequency:	3600 cycles per hour
Rated Control Circuit Voltage (U_c):	50 Hz 100 ... 250 V 60 Hz 100 ... 250 V DC Operation 100 ... 250 V
Operate Time:	Between Coil De-energization and NC Contact Closing 13 ... 98 ms Between Coil De-energization and NO Contact Opening 11 ... 95 ms Between Coil Energization and NC Contact Opening 38 ... 90 ms Between Coil Energization and NO Contact Closing 40 ... 95 ms
Connecting Capacity Main Circuit:	Flexible with Insulated Ferrule 1x 1.5 ... 16 mm ² Flexible with Insulated Ferrule 2x 1.5 ... 16 mm ² Flexible with Ferrule 1/2x 1.5 ... 16 mm ² Rigid 1/2x 1.5 ... 16 mm ²
Connecting Capacity Control	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ²

Circuit:	Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid 1/2x 1 ... 2.5 mm ²
-----------------	--

Wire Stripping Length:	Control Circuit 10 mm Main Circuit 12 mm
-------------------------------	---

Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
------------------------------	--

Terminal Type:	Screw Terminals
-----------------------	-----------------

Environmental

Ambient Air Temperature:	Close to Contactor for Storage -60 ... +80 °C Near Contactor for Operation in Free Air -40 ... +70 °C
---------------------------------	--

Climatic Withstand:	Category B according to IEC 60947-1 Annex Q
----------------------------	---

Maximum Operating Altitude Permissible:	3000 m
--	--------

Resistance to Vibrations acc. to IEC 60068-2-6:	5 ... 300 Hz 4 g closed position / 2 g open position
--	--

Resistance to Shock acc. to IEC 60068-2-27:	Closed, Shock Direction: B1 25 g Open, Shock Direction: B1 5 g Shock Direction: A 30 g Shock Direction: B2 15 g Shock Direction: C1 25 g Shock Direction: C2 25 g
--	--

RoHS Status:	Following EU Directive 2011/65/EU
---------------------	-----------------------------------

Technical UL/CSA

General Use Rating UL/CSA:	(600 V AC) 45 A
-----------------------------------	-----------------

Tightening Torque UL/CSA:	Control Circuit 11 in·lb Main Circuit 22 in·lb
----------------------------------	---

Certificates and Declarations (Document Number)

ABS Certificate:	ABS_15-GE1349500-PDA_90682247
-------------------------	---

BV Certificate:	BV_2634H24898B0
------------------------	---------------------------------

CB Certificate:	CB_SE-80870M1
------------------------	-------------------------------

CCC Certificate:	CCC_2010010304445623
-------------------------	--------------------------------------

Declaration of Conformity - CE:	1SBD250001U1000
--	---------------------------------

DNV Certificate:	DNV-GL_TAE00001AF-1
-------------------------	-------------------------------------

DNV GL Certificate:	DNV-GL_TAE00001AF-1
----------------------------	-------------------------------------

EAC Certificate:	EAC_RU C-FR ME77 B01010
-------------------------	---

Environmental Information:	1SBD250153E1000
-----------------------------------	---------------------------------

GOST Certificate:	GOST_POCCFR.ME77.B07175.pdf
--------------------------	---

Instructions and Manuals:	1SBC101027M6801
----------------------------------	---------------------------------

KC Certificate:	KC_HW02016-15002A
------------------------	-----------------------------------

LR Certificate:	LRS_1300087E1
------------------------	-------------------------------

RINA Certificate:	RINA_ELE084013XG
--------------------------	----------------------------------

RMRS Certificate:	RMRS_1400682124
--------------------------	---------------------------------

RoHS Information:	1SBD251015E1001
--------------------------	---------------------------------

UL Certificate:	UL_20120918-E319322-3-1
------------------------	---

UL Listing Card:	UL_E319322
-------------------------	----------------------------

Container Information

Package Level 1 Units: 1 piece

Package Level 1 Width: 87 mm

Package Level 1 Depth / Length: 103 mm

Package Level 1 Height: 47 mm

Package Level 1 Gross Weight: 0.36 kg

Package Level 1 EAN: 3471523115231

Package Level 2 Units: 36 piece

Package Level 2 Width: 250 mm

Package Level 2 Depth / Length: 300 mm

Package Level 2 Height: 315 mm

Package Level 2 Gross Weight: 12.96 kg

Package Level 3 Units: 864 piece

Classifications

Object Classification Code: Q

E-nummer: 3211511

ETIM 4: EC000066 - Magnet contactor, AC-switching

ETIM 5: EC000066 - Magnet contactor, AC-switching

ETIM 6: EC000066 - Power contactor, AC switching


ETIM 7: EC000066 - Power contactor, AC switching

UNSPSC: 39121529

Contact information


What would you like to do?

I need more information

ABB Sales 

Submit your inquiry

Country / region

United States of America 

Name

Company

E-Mail

Phone

Zip code

Your message

Your local ABB Sales Team

Name

Customer Support

→ [Privacy policy](#)

Cancel

[Send message](#)

▲ Close