Product data sheet Characteristics

SMX120RMBP2U APC Smart-UPS X 120V External Battery Pack Rack/Tower





Overview

Lead time	Usually Ships within 2 Weeks	
-----------	------------------------------	--

General

Provided equipment	Installation guide
	Rack mounting brackets

Physical

,		" 7
Number of rack unit	2U	##
Colour	Black	i
Depth	66.7 cm	
Height	8.5 cm	-4
Net weight	56.36 kg	
Width	43.2 cm	

Environmental

APC	
Overview	
Lead time	Usually Ships within 2 Weeks
General	
Provided equipment	Installation guide Rack mounting brackets
Physical	
Number of rack unit	2U
Colour	Black
Depth	66.7 cm
Height	8.5 cm
Net weight	56.36 kg
Width	43.2 cm
Environmental	
Ambient air temperature for operation	040 °C
Relative humidity	095 %
Operating altitude	010000 ft
Ambient air temperature for storage	-1545 °C
Storage Relative Humidity	095 %
Storage altitude	0.0015240.00 m
Batteries & Runtime	
Number of battery blocks per string	10
Device mounting	Enclosed battery cartridge
Battery type	Lead-acid battery
May 4.0, 2024	

Batteries & Runtime

Number of battery blocks per string	10
Device mounting	Enclosed battery cartridge
Battery type	Lead-acid battery

Number of battery filled slots	0
Number of battery free slots	0
Number of battery replacement quantity	2
Battery voltage	120 V

Packing Units

Package 1 Weight	63.64 kg
Package 1 Height	24.3 cm
Package 1 width	59.6 cm
Package 1 Length	86.9 cm
Number of Units in Package 3	8

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	

Contractual warranty

Warranty	2 years repair or replace