



# DEUTSCH DL AND DBA SERIES CONNECTORS

QUALIFIED TO MIL-DTL-83723 SERIES III

Weight-saving aluminum connectors designed for rugged use and high temperatures

www.pdf.support

# DEUTSCH DL AND DBA SERIES CONNECTORS

Weight-saving connectors designed for rugged use and high temperatures



## WITHSTAND HARSH ENVIRONMENTS

- Triple wire sealed for sealing over a wide range of wire diameters
- Raised moisture barriers around each pin for individual contact sealing

## EASY INSTALLATION

- Bayonet and threaded coupling options
- Closed-entry socket insert for positive pin alignment
- Scoop proof
- Rear release crimp contact system for excellent contact stability
- Visual confirmation of complete coupling

## APPLICATIONS

- Military Aircraft
- Commercial Aircraft
- Communications Equipment
- High-Temperature Industrial Applications

DEUTSCH DL Series bayonet coupling and DBA Series threaded coupling connectors are built to withstand extreme environmental conditions and are qualified to the MIL-DTL-83723 Series III standard.

## MATERIALS

- **Shell**
  - Class A:** Aluminium shell, black anodized finish
  - Class R:** Aluminum shell, electroless nickel finish
  - Class W:** Aluminum shell, olive drab cadmium over nickel base
- **Contacts:** Copper alloy, plated 50  $\mu$ inches selective gold
- **Bayonet Pins:** Passivated stainless steel
- **Insulator:** Rigid plastic dielectric
- **Seals:** Silicone-based elastomer

## ENVIRONMENTAL

- **Temperature:** -65°C to +200°C (Class W -55°C to +175°C)
- **Durability:**
  - 500 mating cycles for all bayonet receptacles (M83723/71 through /76)
  - 250 mating cycles for plugs with RFI fingers (M83723/77 and /78)
  - 250 mating cycles for threaded connectors (M83723/82 through /87)
- **Vibration:** Meets performance requirements of MIL-DTL-83723
- **Shock:** Meets performance requirements of MIL-DTL-83723
- **Shielding:** RFI shielding as per MIL-DTL-83723
- **Conductivity (Voltage Drop):**
  - 5 mV max. (with RFI shielding)
  - 200 mV max. (without RFI shielding)
- **Contact Retention:**
  - Size 20: 20 lb.
  - Size 16: 25 lb.
  - Size 12: 30 lb.
- **Shell Styles:** Square flange, jam nut, straight plug, and RFI plug (RFI plug in Bayonet series only)

## VOLTAGE RATING

Service Rating	Test Voltage ( $V_{rms}$ )		
	@ Sea Level	@ 50,000 ft.	@ 70,000 ft.
I	1500	500	375
II	2300	750	500

**TE Components . . . TE Technology . . . TE Know-how . . .**

AMP | Agastat | CII | Hartman | Kilovac | Microdot | Nanonics | Polamco | Raychem | Rochester | DEUTSCH  
SEACON Phoenix | L.L. Rowe | Phoenix Optix | SEACON

Get your product to market faster with a smarter, better solution.



## Bayonet Coupling Connectors

### MIL-DTL-83723 Series III System

**M83723/ 72 R 22 55 N**

**Military Designation** \_\_\_\_\_

**Shell Type** \_\_\_\_\_

- 71** Square Flange Mount Receptacle, Socket Contacts
- 72** Square Flange Mount Receptacle, Pin Contacts
- 73** Jam Nut Receptacle, Socket Contacts
- 74** Jam Nut Receptacle, Pin Contacts
- 75** Straight Plug, Socket Contacts
- 76** Straight Plug, Pin Contacts
- 77** RFI Grounding Plug, Socket Contacts (Not Available in A Class)
- 78** RFI Grounding Plug, Pin Contacts (Not Available in A Class)

**Class (Material and Finish)** \_\_\_\_\_

- A** Aluminum Shell, Black Anodized Finish
- R** Aluminum Shell, Electroless Nickel Finish
- W** Aluminum Shell, Olive Drab Cadmium over Nickel Base

**Shell Size** \_\_\_\_\_

**8, 10, 12, 14, 16, 18, 20, 22, 24**

**Insert Arrangement** \_\_\_\_\_

See insert arrangement table

**Clocking/Keying Position** \_\_\_\_\_

- N** Normal
- 6, 7, 8, 9, Y** (Y Not Available in Size 8 Shell)

### DEUTSCH DL Series System

**DL 66 R 18 14 P 8 6116**

**Connector Series** \_\_\_\_\_

**Shell Mounting Style** \_\_\_\_\_

- 60** Square Flange
- 64** Jam Nut
- 66** Straight Plug
- 68** RFI Plug

**Class** \_\_\_\_\_

- R** Nonconductive Finish (Black Anodized)
- G** Conductive Finish (Nickel)

**Shell Size** \_\_\_\_\_

**8, 10, 12, 14, 16, 18, 20, 22, 24**

**Insert Arrangement** \_\_\_\_\_

See insert arrangement table

**Contact Style** \_\_\_\_\_

- P** Pin
- S** Socket

**Clocking/Keying Position** \_\_\_\_\_

**N, 6, 7, 8, 9, 10** (10 Not Available in Size 8 Shell)  
(Consult TE for available alternate clocking)

**Modification** \_\_\_\_\_

- 6116** Black Anodized Finish, Blue Color Bands, Less Backshell
- 6106** Electroless Nickel Finish, Blue Color Bands, Less Backshell
- 6117** Olive Drab Cadmium over Nickel Base, Blue Color Bands, Less Backshell



### Insert Arrangements For Bayonet Connectors

Inserts are QPL and available in 6, 7, 8, 9, or Y polarization (Insert 8-3 is not available with Y polarization)

Consult TE for insert arrangements for threaded connectors.

Arrangement	No. of Contacts		
	Size 20	Size 16	Size 12
8-3	4		
10-2	3		
10-5	6		
10-6	7		
10-20		3	
12-3		4	
12-12	14		
14-04			5
14-07		8	
14-12		4	
14-15	17		
16-10		11	
16-24	27		
18-8			9
18-14		16	
18-31	35		
20-16		18	
20-25	21		1
20-28	27		5
20-39	41	3	
20-41	46		
22-12			14
22-19		21	
22-32	29		7
22-39	30	14	
22-55	61		
24-19			21
24-43	26	22	
24-57	61		3
24-61	68		



## Threaded Connectors

### MIL-DTL-83723 Series III System

**M83723 84 R 22 55 N**

**Military Designation** \_\_\_\_\_

**Shell Type** \_\_\_\_\_

- 82** Square Flange Mount Receptacle, Socket Contacts
- 83** Square Flange Mount Receptacle, Pin Contacts
- 84** Jam Nut Receptacle, Socket Contacts
- 85** Jam Nut Receptacle, Pin Contacts
- 86** Straight Plug, Socket Contacts
- 87** Straight Plug, Pin Contacts

**Class (Material and Finish)** \_\_\_\_\_

- A** Aluminum Shell, Black Anodized Finish
- R** Aluminum Shell, Electroless Nickel Finish
- W** Aluminum Shell, Olive Drab Cadmium over Nickel Base

**Shell Size** \_\_\_\_\_

**8, 10, 12, 14, 16, 18, 20, 22, 24**

**Insert Arrangement** \_\_\_\_\_

Consult TE

**Clocking/Keying Position** \_\_\_\_\_

- N** Normal
- 6, 7, 8, 9, Y** (Y Not Available in Size 8 Shell)

### DEUTSCH DBA Series System

**DBA 34 - 22-55 P N 6116**

**Connector Series** \_\_\_\_\_

**Style** \_\_\_\_\_

- 30** Square Flange Receptacle (/82, Socket; /83, Pin)
- 34** Jam Nut Receptacle (/84, Socket; /85, Pin)
- 36** Plug (/86, Socket; /87, Pin)

**Shell Size** \_\_\_\_\_

**8, 10, 12, 14, 16, 18, 20, 22, 24**

**Insert Arrangement** \_\_\_\_\_

Consult TE

**Pin or Socket** \_\_\_\_\_

- P** Pin
- S** Socket

**Clocking Position** \_\_\_\_\_

Shell Clocking: **N, 6, 7, 8, 9, 10** (10 Not Available in Size 8 Shell)

**Modification** \_\_\_\_\_

- 6116** Aluminum Shell, Black Anodized Finish
- 6106** Aluminum Shell, Electroless Nickel Finish
- 6117** Aluminum Shell, Olive Drab Cadmium over Nickel Base

## For More Information

### TE Technical Support Center

North America	+1 800 522 6752
Asia Pacific	+86 0 400 820 6015
Austria	+43 1 905 601 228
Baltic Regions	+46 8 5072 5000
Benelux	+31 73 6246 999
Czech Republic	+420 800 701 462
France	+33 1 34 20 86 86
Germany	+49 6251 133 1999
Hungary	+36 809 874 04
Italy	+39 011 401 2632
Nordic	+46 8 5072 5000
Poland	+48 800 702 309
Russia	+7495 790 790 2
Spain/Portugal	+34 93 2910366
Switzerland	+41 52 633 66 26
United Kingdom	+44 800 267 666

Follow us on Twitter for all the latest product news  
@TEConnectivity, and on Facebook, TEConnectivity.

[te.com/deutsch](http://te.com/deutsch)

© 2015 TE Connectivity Ltd. family of companies. All Rights Reserved.

1-1773863-9 ADM/RRD 1.5M 10/2015

DEUTSCH, TE, TE Connectivity and the TE connectivity (logo) are trademarks of the TE Connectivity Ltd. family of companies.

Other products, logos, and company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information herein, nothing herein constitutes any guarantee that such information is error-free, or any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. The TE entity issuing this publication reserves the right to make any adjustments to the information contained herein at any time without notice. All implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose are expressly disclaimed. The dimensions herein are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice.

Consult TE for the latest dimensions and design specifications.