

DO-41 Zener Diodes (1.3 W)

Electrical Characteristics (At Ta=25°C, Unless Otherwise Specified)																
Type No.	V _{ZT} at I _{ZT}			r _{ZT} at I _{ZT}		I _{ZT}	r _{ZK} at I _{ZK}		I _{ZK}	Temp. Coeff. of Zener Voltage typ (%/°C)	I _R at V _R Ta 25°C max (µA)	V _R	I _{ZM}	I _{ZSM}	P _D	V _F @ I _F
	min	nom	max (V)	max	(mΩ)	(mA)	max	(mΩ)	(mA)		(V)	(mA)	(mA)	(W)	max (V)	(mA)
BZX85C2V7	2.5	2.9	20	80	400	1	-0.07	150	1	370	2874	1.3	1	200		
BZX85C3V0	2.8	3.2	20	80	400	1	-0.07	100	1	340	2604	1.3	1	200		
BZX85C3V3	3.1	3.5	20	80	400	1	-0.06	40	1	320	2381	1.3	1	200		
BZX85C3V6	3.4	3.8	20	70	500	1	-0.06	20	1	290	2193	1.3	1	200		
BZX85C3V9	3.7	4.1	15	60	500	1	-0.05	10	1	280	2033	1.3	1	200		
BZX85C4V3	4	4.6	13	50	500	1	-0.03	3	1	250	1812	1.3	1	200		
BZX85C4V7	4.4	5	13	45	500	1	-0.01	3	1	215	1667	1.3	1	200		
BZX85C5V1	4.8	5.4	10	45	500	1	+0.01	1	1.5	200	1543	1.3	1	200		
BZX85C5V6	5.2	6	7	45	400	1	+0.03	1	2	190	1389	1.3	1	200		
BZX85C6V2	5.8	6.6	4	35	300	1	+0.04	1	3	170	1263	1.3	1	200		
BZX85C6V8	6.4	7.2	3.5	35	300	1	+0.05	1	4	155	1157	1.3	1	200		
BZX85C7V5	7	7.9	3	35	200	0.5	+0.05	1	4.5	140	1055	1.3	1	200		
BZX85C8V2	7.7	8.7	5	25	200	0.5	+0.06	1	6.2	130	958	1.3	1	200		
BZX85C9V1	8.5	9.6	5	25	200	0.5	+0.06	1	6.8	120	868	1.3	1	200		
BZX85C10	9.4	10.6	7.5	25	200	0.5	+0.07	0.5	7	105	786	1.3	1	200		
BZX85C11	10.4	11.6	8	20	300	0.5	+0.07	0.5	8.2	97	718	1.3	1	200		
BZX85C12	11.4	12.7	9	20	350	0.5	+0.07	0.5	9.1	88	656	1.3	1	200		
BZX85C13	12.4	14.1	10	20	400	0.5	+0.07	0.5	10	79	591	1.3	1	200		
BZX85C15	13.8	15.6	15	15	500	0.5	+0.08	0.5	11	71	534	1.3	1	200		
BZX85C16	15.3	17.1	15	15	500	0.5	+0.08	0.5	12	66	487	1.3	1	200		
BZX85C18	16.8	19.1	20	15	500	0.5	+0.08	0.5	13	62	436	1.3	1	200		
BZX85C20	18.8	21.2	24	10	600	0.5	+0.08	0.5	15	56	393	1.3	1	200		
BZX85C22	20.8	23.3	25	10	600	0.5	+0.08	0.5	16	52	358	1.3	1	200		
BZX85C24	22.8	25.6	25	10	600	0.5	+0.08	0.5	18	47	326	1.3	1	200		
BZX85C27	25.1	28.9	30	8	750	0.25	+0.09	0.5	20	41	288	1.3	1	200		
BZX85C30	28	32	30	8	1000	0.25	+0.09	0.5	22	36	260	1.3	1	200		
BZX85C33	31	35	35	8	1000	0.25	+0.09	0.5	24	33	238	1.3	1	200		
BZX85C36	34	38	40	8	1000	0.25	+0.09	0.5	27	30	219	1.3	1	200		
BZX85C39	37	41	50	6	1000	0.25	+0.09	0.5	30	28	203	1.3	1	200		
BZX85C43	40	46	50	6	1000	0.25	+0.09	0.5	33	26	181	1.3	1	200		
BZX85C47	44	50	90	4	1500	0.25	+0.09	0.5	36	23	167	1.3	1	200		