



POS. AND DIMENSIONS:

| PIN | DIM.(mm) | | | | PIN | DIM.(mm) | | | |
|-----|----------|-------|------|------|-----|----------|-------|-------|-------|
| | A | B | C | D | | A | B | C | D |
| 02 | 4.40 | 1.80 | 2.20 | 2.20 | 12 | 8.80 | 12.40 | 9.80 | 10.20 |
| 03 | 1.60 | 5.20 | 2.60 | 3.00 | 13 | 9.60 | 13.20 | 10.60 | 11.00 |
| 04 | 2.40 | 6.00 | 3.40 | 3.80 | 14 | 10.40 | 14.00 | 11.40 | 11.80 |
| 05 | 3.20 | 6.80 | 4.20 | 4.60 | 15 | 11.20 | 14.80 | 12.20 | 12.60 |
| 06 | 4.00 | 7.60 | 5.00 | 5.40 | 16 | 12.00 | 15.60 | 13.00 | 13.40 |
| 07 | 4.80 | 8.40 | 5.80 | 6.20 | 17 | 12.80 | 16.40 | 13.80 | 14.20 |
| 08 | 5.60 | 9.20 | 6.60 | 7.00 | 18 | 13.60 | 17.20 | 14.60 | 15.00 |
| 09 | 6.40 | 10.00 | 7.40 | 7.80 | 19 | 14.40 | 18.00 | 15.40 | 15.80 |
| 10 | 7.20 | 10.80 | 8.20 | 8.60 | 20 | 15.20 | 18.80 | 16.20 | 16.60 |
| 11 | 8.00 | 11.60 | 9.00 | 9.40 | | | | | |

- NOTES:
1. MATERIAL(HALOGEN FREE): LCP, UI94V-0 (CREAM)
 2. GLOW WIRE COMPATIBLE.
 3. USE WITH: 10145493 CRIMP TERMINAL
 4. MATE WITH HEADER: 10144041, 10144042
 5. PRODUCT SPEC: GS-12-1444
 6. PACKAGING SPEC: GS-14-2616
 7. ORDERING CODE: 10145492-XXLF

PIN NO.
02~20

| | | | | | | | |
|---------------------------------------|------------|---------------------------------------|------------|--------------|--------------------------|----------------|--------------------|
| mat'l. code | ISO 1302 | tolerance | ISO 406 | ISO 1101 | projection | product family | MINITEK |
| tolerances unless otherwise specified | 0±x | tolerances unless otherwise specified | 0.0±.25 | 1101 | mm | title | 0.8MM RECE HOUSING |
| dr | TONY LENG | date | 2017-09-13 | scale | 1:1 | dwg no | 10145492 |
| engr | JASON WANG | chr | L.Q. Lei | sheet 1 of 1 | size | A3 | |
| pppd | TIM YAO | revision | B | type | Product Customer Drawing | | |
| sheet index | sheet 1 | | | | | | |