

High Voltage Transistors

TYPE NO.	POLARITY	CASE	MAXIMUM RATINGS			H _{FE}				V _{CE(SAT)}		f _T min (MHz)	Cob Cre • max (pF)
			P _d (mW)	I _C (mA)	V _{CEO} (V)	min	max	I _C (mA)	V _{CE} (V)	max (V)	I _C (mA)		
BFS89	N	TO-39	580	100	300	25	—	50	10	1	30	90+	3+ •
BFS90	P	TO-39	800	100	140	30	—	10	10	1	30	—	—
BFS91	P	TO-39	800	100	80	40	—	10	10	0.5	10	—	—
BFT47	N	TO-39	5000▲	100	160	25	—	30	10	1	30	50	—
BFT48	N	TO-39	5000▲	100	250	25	—	30	10	1	30	50	—
BFT49	N	TO-39	5000▲	100	300	25	—	30	10	1	30	50	—
BFT57	N	TO-18	360	200	160	25	—	30	10	1	30	110+	5.5+
BFT58	N	TO-18	360	200	250	25	—	30	10	1	30	110+	5.5+
BFT59	N	TO-18	360	200	300	25	—	30	10	1	30	110+	5.5+
BFW43	P	TO-18	400	100	150	40	—	10	10	0.5	10	60	7
BFW44	P	TO-39	700	100	150	40	—	10	10	0.5	10	60	7
BFW45	N	TO-39	800	50	130	20	120	50	20	10	50	80	6
BFX98	N	TO-39	800	100	150	30	—	25	10	1	25	40	8
BFY57	N	TO-39	800	100	125	30	150	30	10	1.5	50	40	12
BFY80	N	TO-18	500	100	90	30	—	2	10	0.9	2	50	8
BSS38	N	TO-92F	300◆	100	80	20	—	4	1	0.7	4	60	—
BSV68	P	TO-18	250	100	100	30	—	25	5	0.25	25	50	5
BSY79	N	TO-18	300	30	120	30	—	1	1	0.5	2	100+	4+
MH7301	N	TO-220	1250	100	160	40	—	30	10	1.5	30	50	5
MH7302	N	TO-220	1250	100	200	40	—	30	10	1.5	30	50	5
MH7303	N	TO-220	1250	100	250	40	—	30	10	1.5	30	50	5
MPSA42	N	TO-92A	625	100	300	40	—	30	10	0.5	20	50	3
MPSA43	N	TO-92A	625	100	200	50	200	30	10	0.4	20	50	4
MPSA92	P	TO-92A	625	500	300	25	—	30	10	0.5	20	50	6 •
MPSA93	P	TO-92A	625	500	200	25	—	30	10	0.4	20	50	8 •
MPSD01	N	TO-92A	625	100	200	20	—	30	10	—	—	40	3+
MPSD02	N	TO-92A	350	50	140	25	—	10	10	—	—	40	—
MPSD03	N	TO-92A	350	50	140	25	—	10	10	—	—	40	—
MPSD52	P	TO-92A	350	50	140	25	—	10	10	—	—	40	—
MPSD53	P	TO-92A	350	50	100	25	—	10	10	—	—	40	—
MPSL01	N	TO-92A	500	100	120	50	300	10	5	0.3	50	60	8
MPSL51	P	TO-92A	625	600	100	40	250	50	5	0.3	50	60	8
P038	P	TO-92B	600	500	300	25	200	0.2	0.5	0.5	1	35	—
P039	N	TO-92B	600	500	300	25	150	100	1	0.3	200	10	—
2N3114	N	TO-39	800	200	150	30	120	30	10	1	50	40	9
2N3634	P	TO-39	600	100	140	50	150	50	10	0.5	50	150	10
2N3742	N	TO-39	1000	100	300	20	200	30	10	1	10	30	6
2N3743	N	TO-39	1000	50	300	25	250	30	10	8	30	30	15
2N3923	N	TO-39	800	1000	150	30	120	25	10	1	25	40	3.5
2N4926	N	TO-39	1000	50	200	20	200	30	10	1	10	30	6
2N4927	N	TO-39	1000	50	250	20	200	30	10	1	10	30	6
2N4928	P	TO-39	600	100	100	25	200	10	10	0.5	10	100	6
2N5058	N	TO-39	1000	150	300	35	150	30	25	1	30	30	10
2N5059	N	TO-39	1000	150	250	30	150	30	25	1	30	30	10
2N5400	P	TO-92A	350	600	120	40	180	10	5	0.5	50	100	6
2N5401	P	TO-92A	350	600	150	60	240	10	5	0.5	50	100	6
2N5550	N	TO-92A	350	600	140	60	250	10	5	0.25	50	100	6
2N5551	N	TO-92A	350	600	160	80	250	10	5	0.2	50	100	6
2N6733	P	TO-237A	2500▲	100	200	40	200	10	10	2	20	50	—
2N6734	P	TO-237A	2500▲	100	250	40	200	10	10	2	20	50	—
2N6735	P	TO-237A	2500▲	100	300	40	200	10	10	2	20	50	—

▲T_c = 25°C + Typical value ◆TA = 75°C