

# AC/DC Current Probes

## TCP0020 • TCP2020 • TCP202A Datasheet



TCP0020 AC/DC Current Probe.

### Features & Benefits

- Easy-to-Use and Accurate AC/DC Current Measurements
- DC to >50 MHz Bandwidth
- Core Jaw Diameter of 5 mm (0.2 in.)
- Accurately Measures Current Levels as Low as 10 mA per Division
- High Accuracy with Typically Less than 1% DC Gain Error
- Split-core Construction allows Easy Circuit Connection
- Low Noise and DC Drift

- TCP0020
  - 20 A<sub>RMS</sub> Maximum Current Capability
  - 100 A Peak Pulse Current Capability
  - Connects Directly to Oscilloscopes with the TekVPI™ Probe Interface
  - Provides Automatic Units Scaling and Readout on the Oscilloscope Display
  - One-button Degauss and AutoZero Control for Ease of Use
  - Easy Access to Scope-displayed Probe Menu for Probe Setup Control and Operating Status Information
  - Remote Control Capability through TekVPI Oscilloscope
- TCP2020
  - 20 A<sub>RMS</sub> Maximum Current Capability
  - 100 A Peak Pulse Current Capability
  - 10 mA/mV Sensitivity
  - BNC Output Connects to Most Oscilloscopes and Other Measurement Equipment (>100 kΩ Termination Required)
  - Degauss Button and Thumbwheel for DC Offset Adjustment
  - Powered by an AC Adapter
- TCP202A
  - 15 A<sub>DC + Peak AC</sub> Maximum Current Capability
  - 50 A Peak Pulse Current Capability
  - Connects Directly to Oscilloscopes with the TekProbe™ Interface
  - Provides Automatic Units Scaling and Readout on the Oscilloscope Display
  - Degauss Button and Thumbwheel for DC Offset Adjustment
- Safety Certified

### Applications

- Power Supplies
- Semiconductor Devices
- Power Inverter/Converters
- Electronic Ballasts
- Industrial/Consumer Electronics
- Mobile Communications
- Motor Drives
- Transportation Systems

## TCP0020, TCP2020, TCP202A

The TCP0020, TCP2020, and TCP202A are a family of high-performance, easy-to-use AC/DC current probes designed for use with a variety of oscilloscopes. The TCP0020 is designed for direct connection to oscilloscopes with the TekVPI™ probe interface and the TCP202A is designed for direct connection to oscilloscopes with the TekProbe™ probe interface. The TCP2020 is designed for use with any instrument with BNC inputs and >100 kΩ input termination.

These AC/DC current probes provide sufficient performance to support 50 MHz measurement system bandwidth. The TCP0020 and TCP2020 provide a maximum 20 A<sub>RMS</sub> measurement range, while the TCP202A provides a maximum 15 A<sub>DC + Peak AC</sub> measurement range. These probes also provide excellent accuracy to current levels as low as 10 mA, important for meeting today's challenging current measurement needs.

### Characteristics

#### General

| Characteristic         | Description   |
|------------------------|---|
| Bandwidth              | DC to ≥50 MHz   |
| Rise Time              | ≤7 ns   |
| Max Current            | 20 A <sub>RMS</sub> (TCP0020 and TCP2020)<br>15 A <sub>DC + Peak AC</sub> (TCP202A) |
| Max Peak Pulse Current | 100 A (TCP0020 and TCP2020)<br>50 A (TCP202A)                                       |
| Maximum Sensitivity    | 10 mA (on oscilloscopes that support 1 mV/div setting)                              |
| Coupling               | DC coupling only  |
| Max Bare-wire Voltage  | 150 V CAT II (300 V CAT II Insulated Wire)  |

#### Typical

| Characteristic         | Description   |
|------------------------|---|
| DC Accuracy            | ±1% typical, ±3% warranted                                |
| Max Amp-second Product | 1000 A*μs (TCP0020 and TCP2020)<br>500 A*μs (TCP202A)     |
| Insertion Impedance    | 0.036 Ω at 1 MHz<br>0.117 Ω at 10 MHz<br>0.54 Ω at 50 MHz |
| Signal Delay           | 17 ns   |

### Environmental

| Characteristic | Description  |
|----------------|--|
| Temperature    |  |
| Operating      | 0 °C to +50 °C   |
| Nonoperating   | -40 °C to +75 °C   |
| Humidity       |  |
| Operating      | 5% to 95% RH, tested up to +30 °C (+86 °F)<br>5% to 85% RH, tested at +30 °C to +50 °C (+86 °F to +122 °F) |
| Nonoperating   | 5% to 95% RH, tested up to +30 °C (+86 °F)<br>5% to 85% RH, tested at +30 °C to +75 °C (+86 °F to +167 °F) |
| Regulatory     |  |
| Safety         | CSA1010.1:1997, CSA1010.2:032-96, IEC61010-1:2001, IEC61010-2-032  |

### Physical Characteristics

| Probe Head Size  | mm    | in.          |
|------------------|-------|--------------|
| Height           | 30.5  | 1.2          |
| Width            | 15.2  | 0.6          |
| Length           | 148   | 5.8          |
| Other Dimensions | m     | in.          |
| Cable Length     | 2     | 79           |
| Weight           | kg    | lb.          |
| Probe Only       | 0.227 | 0.5          |
| Shipping         | 1.22  | 2 lb. 11 oz. |

### Power Requirements

TCP0020 is powered directly by oscilloscopes with the TekVPI™ probe interface. TCP2020 is powered by AC adapter. (Specify power plug option when ordering.) TCP202A is powered directly by oscilloscopes with the TekProbe™ probe interface or through the TekVPI™ probe interface when used with the TPA-BNC adapter.

### Standard Warranty

One-year parts and labor.

## Ordering Information

### TCP0020

AC/DC Current Probe.

**Includes:** Instruction Manual (English) (071-3002-xx), Probe Ground Lead – 6 in. length (196-3120-xx), Nylon Carrying Case (016-1952-xx).

### TCP2020

AC/DC Current Probe.

**Includes:** Instruction Manual (English) (071-3002-xx), Probe Ground Lead – 6 in. length (196-3120-xx), Nylon Carrying Case (016-1952-xx), AC Adapter (specify power plug option when ordering).

### TCP202A

AC/DC Current Probe.

**Includes:** Instruction Manual (English) (071-3002-xx), Probe Ground Lead – 6 in. length (196-3120-xx), Nylon Carrying Case (016-1952-xx).

### Power Plug Options (TCP2020 Only)

| Option   | Description                          |
|----------|--------------------------------------|
| Opt. A0  | North America Power, 115 V, 60 Hz    |
| Opt. A1  | Universal Euro Power, 220 V, 50 Hz   |
| Opt. A2  | United Kingdom Power, 240 V, 50 Hz   |
| Opt. A3  | Australia Power, 240 V, 50 Hz        |
| Opt. A5  | Switzerland Power, 220 V, 50 Hz      |
| Opt. A6  | Japan Power, 100 V, 110/120 V, 60 Hz |
| Opt. A10 | China Power, 50 Hz                   |
| Opt. A11 | India Power, 50 Hz                   |
| Opt. A12 | Brazil Power, 60 Hz                  |
| Opt. A99 | No Power Cord                        |

## Service Options

| Option  | Description                                    |
|---------|--|
| Opt. C3 | Calibration Service 3 Years                    |
| Opt. C5 | Calibration Service 5 Years                    |
| Opt. D1 | Calibration Data Report                        |
| Opt. D3 | Calibration Data Report 3 Years (with Opt. C3) |
| Opt. D5 | Calibration Data Report 5 Years (with Opt. C5) |
| Opt. R3 | Repair Service 3 Years                         |
| Opt. R5 | Repair Service 5 Years                         |

## Recommended Accessories

| Accessory   | Description  |
|-------------|--|
| 067-2396-xx | Current Loop, 1 Turn, 50 $\Omega$ with BNC connector used for performance verification |
| 067-1686-xx | Deskew/Calibration Fixture   |

**Contact Tektronix:**

- ASEAN / Australasia** (65) 6356 3900
- Austria** 00800 2255 4835\*
- Balkans, Israel, South Africa and other ISE Countries** +41 52 675 3777
- Belgium** 00800 2255 4835\*
- Brazil** +55 (11) 3759 7627
- Canada** 1 800 833 9200
- Central East Europe and the Baltics** +41 52 675 3777
- Central Europe & Greece** +41 52 675 3777
- Denmark** +45 80 88 1401
- Finland** +41 52 675 3777
- France** 00800 2255 4835\*
- Germany** 00800 2255 4835\*
- Hong Kong** 400 820 5835
- India** 000 800 650 1835
- Italy** 00800 2255 4835\*
- Japan** 81 (3) 6714 3010
- Luxembourg** +41 52 675 3777
- Mexico, Central/South America & Caribbean** 52 (55) 56 04 50 90
- Middle East, Asia, and North Africa** +41 52 675 3777
- The Netherlands** 00800 2255 4835\*
- Norway** 800 16098
- People's Republic of China** 400 820 5835
- Poland** +41 52 675 3777
- Portugal** 80 08 12370
- Republic of Korea** 001 800 8255 2835
- Russia & CIS** +7 (495) 7484900
- South Africa** +41 52 675 3777
- Spain** 00800 2255 4835\*
- Sweden** 00800 2255 4835\*
- Switzerland** 00800 2255 4835\*
- Taiwan** 886 (2) 2722 9622
- United Kingdom & Ireland** 00800 2255 4835\*
- USA** 1 800 833 9200

\* European toll-free number. If not accessible, call: +41 52 675 3777

Updated 10 February 2011

**For Further Information.** Tektronix maintains a comprehensive, constantly expanding collection of application notes, technical briefs and other resources to help engineers working on the cutting edge of technology. Please visit [www.tektronix.com](http://www.tektronix.com)



Copyright © Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.

11 Jul 2012

51W-28098-0



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Tektronix:](#)

[TCP202A](#) [TCP202A D1](#) [TCP2020](#)