GS-12-625		Product Specification	FÇ	
TITLE			PAGE 1 of 8	REVISION D
To	erminal block- Pl	ug and Socket, Fixed Plug	AUTHORIZED BY  Jason Hsu	Nov. 11 <sup>th</sup> , 2009
			CLASSIFICATION Unrestri	cted

#### 1.0 **SCOPE**

This specification covers performance, test, and quality requirement for terminal block pluggable plug, socket and fixed plug. Centerline spacing are 3.50, 3.81, 5.00, 5.08, and 7.62mm.

#### 2.0 **APPLICABLE DOCUMENTS**

#### 2.1 **Drawing**

	Pitch	Туре	FCI series name	Drawing number	FCI part number	Poles
			01-350	20020004	20020004-CxxxxxLF	02~24p
		Dlug	01-350	20020000	20020000-CxxxxxLF	02~24p
		Plug	02-350	20020009	20020009-CxxxxxLF	02~24p
9	3.50mm		02-350	20020008	20020008-CxxxxxLF	02~24p
J			06-350	20020107	20020107-CxxxxxxLF	02~24p
		Cooket	06-350	20020108	20020108-CxxxxxxLF	02~24p
		Socket	06-350	20020111	20020111-CxxxxxLF	02~24p
			06-350	20020110	20020110-CxxxxxLF	02~24p
			01-381	20020004	20020004-DxxxxxxLF	02~24p
		Dive	01-381	20020000	20020000-DxxxxxxLF	02~24p
		Plug	02-381	20020009	20020009-DxxxxxxLF	02~24p
	04		02-381	20020008	20020008-DxxxxxxLF	02~24p
3	3.81mm		06-381	20020107	20020107-DxxxxxxLF	02~24p
		Socket	06-381	20020108	20020108-DxxxxxxLF	02~24p
			06-381	20020111	20020111-DxxxxxxLF	02~24p
			06-381	20020110	20020110-DxxxxxxLF	02~24p
			01-500	20020006	20020006-GxxxxxxLF	02~24p
		Diva	01-500	20020003	20020003-GxxxxxxLF	02~24p
		Plug	02-500	20020009	20020009-GxxxxxxLF	02~24p
			02-500	20020008	20020008-GxxxxxxLF	02~24p
9	.00mm		06-500	20020107	20020107-GxxxxxxLF	02~24p
			06-500	20020108	20020108-GxxxxxxLF	02~24p
		Socket	06-500	20020110	20020110-GxxxxxxLF	02~24p
			06-500	20020111	20020111-GxxxxxxLF	02~24p
			01-508	20020003	20020003-HxxxxxxLF	02~24p
			01-508	20020006	20020006-HxxxxxxLF	02~24p
5	.08mm	Plug	02-508	20020009	20020009-HxxxxxxLF	02~24p
			06-508	20020108	20020108-HxxxxxxLF	02~24p
			06-508	20020111	20020111-HxxxxxxLF	02~24p

Rev: E STATUS: Released Printed: Mar 05, 20:
This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on the document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.

GS-01-001

Form E-3005 Rev F

GS-12-625	Product Specification	FC	
TITLE		PAGE 2 of 8	REVISION D
Terminal bloc	k- Plug and Socket, Fixed Plug	AUTHORIZED BY  Jason Hsu	Nov. 11 <sup>th</sup> , 2009
		CLASSIFICATION Unrestr	cted

i	1	1	ı	1	
		02-508	20020008	20020008-HxxxxxLF	02~24p
	Socket	06-508	20020107	20020107-HxxxxxxLF	02~24p
	Socker	06-508	20020110	20020110-HxxxxxxLF	02~24p
	Diva	04-762	20020516	20020516-MxxxxxxLF	02~16p
	Plug	04-762	20020517	20020517-MxxxxxxLF	02~16p
		07-762	20020618	20020618-MxxxxxxLF	02~16p
7.62mm		07-762	20020619	20020619-MxxxxxxLF	02~16p
	Socket	07-762	20020620	20020620-MxxxxxxLF	02~16p
		07-762	20020621	20020621-MxxxxxxLF	02~16p
		07-762	20020622	20020622-MxxxxxxLF	02~16p
3.50mm		26-350	20020327	20020327-CxxxxxxLF	02~24p
3.81mm		26-381	20020327	20020327-DxxxxxxLF	02~24p
5.00mm	Fixed	21-500	20020316	20020316-GxxxxxxLF	02~24p
5.08mm	Plug	21-508	20020316	20020316-HxxxxxxLF	02~24p
3.00111111		21-508	20020336	20020336-HxxxxxxLF	04~05p
7.62mm		12-762	20020705	20020705-MxxxxxxLF	02~03p

### 2.2 Other Standard and Specification

- 4.2.1 IEC 60998-1: Connecting Devices for Low Voltage Circuits for Household and Similar Purposes. Part 1: General Requirements.
- 4.2.2 IEC 60998-2-1: Connecting Devices for Low Voltage Circuits for Household and Similar Purposes. Part 2-1: Particular Requirements for Connecting Device as Separate Entities with Screw-type Clamping Units.
- 4.2.3 UL 1059: Terminal Blocks
- 4.2.4 EIA-364:

Electrical Connector/Socket Test Procedure Including Environmental Classifications

### 2.3 FCI SPECIFICATIONS

disclosed to others without the written consent of FCI. Copyright FCI.

4.3.1 GES-03-601 Current Rating

4.3.2 GS-14 -1394 Package Specification

PDS: Rev: E

STATUS: Released

Printed: Mar 05, 2012

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on the document may be used in any way or

GS-12-625		Product Specification	FC	
TITLE			PAGE 3 of 8	REVISION D
Te	erminal block- Pl	ug and Socket, Fixed Plug		Nov. 11 <sup>th</sup> , 2009
			CLASSIFICATION Unrestric	cted

#### 3.0 **REQUIREMENTS**

#### 3.1 **Design and Construction**

Connectors shall be of the design, construction and physical dimensions specified on the applicable product drawings and shall consider the requirements mentioned on IEC 998-2-1 paragraph 10, relevant to clamping units.

#### 3.2 **Materials, Dimensions, Plating and Markings**

All of these items are described on the individual drawings.

#### 3.3 Ratings

Voltage rating, current rating, operation temperature and rated screw torque are described on the individual drawings.

#### 3.4 **Performance and Test Description**

Product is designed to meet the electrical, mechanical and environment performance requirement list in section 3.5.

Unless otherwise specified, all tests shall be performed at ambient environmental conditions per IEC 160.

3.5 **Test Requirements and Procedures Summary** 

3.5.1 ELECTRICAL REQUIREMENTS					
DESCRIPTION	TEST CONDITION	REQUIREMENT			
3.5.1.1 Product Examination	Visual, dimensional and functional	Meet requirements of product drawing.			
3.5.1.2 Low Level Contact Resistance	Mated connectors, apply a maximum voltage of 0.2 V between wire pole and terminated terminal.	20 milliohms maximum.			
3.5.1.3 Insulation resistance	IEC 60998-1, paragraph 13e 13.3. Initial 1000Volts DC, or 500Volts DC after environment test applied between two adjacent contact with measurements made 1 minute after the application of the voltage.	<ol> <li>5000 MΩ Min. initial.</li> <li>5 MΩ minimum after environment test.</li> </ol>			
3.5.1.4 Dielectric Withstanding Voltage	IEC 60998-1, paragraph 13e 13.4. Apply 1.6K VAC, Test between adjacent contacts of connector assemblies.	No breakdown; Current leakage<5 mA			

Rev: E STATUS: Released Printed: Mar 05, 20:
This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on the document may be used in any way or

GS-01-001 Form E-3005

disclosed to others without the written consent of FCI. Copyright FCI.

NUMBER GS-12-625		Product Specification	FC	
020 12 020			3	
TITLE			PAGE	REVISION
			4 of 8	D
	Terminal block- P	lug and Socket, Fixed Plug	AUTHORIZED BY	DATE
			Jason Hsu	Nov. 11 <sup>th</sup> , 2009
			CLASSIFICATION	!atad
			Unrestr	ıctea

3.5.1.5	UL 1059	+30 °C Maximum
Temperature rise	Measurements are made when the specimen had reached	100 C Maximum
VS current	thermal equilibrium at the rated current specified on	
	individual drawing.	

3.5.2			
MECHANICAL REC DESCRIPTION	TEST CONDITION	REQUIREMENT	Applicable
3.5.2.1	Mate connector and measure the force	5.5N Maximum.	Plug/socket
Mating force	required.	(Per mating pole.)	
3.5.2.2	Unmate connector and measure the force	1.0N Minimum.	Plug/socket
Unmating force	required.	(Per unmating pole.)	
3.5.2.3	After durability cycles, low level contact	200 Cycles	Plug/socket
Durability	resistance shall be less than 20millionohm.		
(mate/unmate)			
3.5.2.4	IEC 60998-2-1 paragraph 10.105,	10AWG: Min 80N	Plug/Fixed
Wire Pull Strength	Subject connector to a pull force for 1 minute	12AWG: Min 60N	plug
	in the axis of tapping connector.	16AWG: Min 30N	
	Connector shall not slip out of the connecting	24AWG: Min 13N	
	device.		
3.5.2.5	UL1059	No visible crack	Plug/Fixed
Torque	Apply the rated torque (refer to drawings) for		Plug
	wire attachment.		
3.5.2.6	Force required to unload pin from the housing	Min 20N.	Socket
Pin Retention	in the direction of plug entry.		
3.5.2.7	Soldering time 5 second. (flux is applied)	95% min of solder area and	Fixed
Solder ability	Soldering temperature: 250±10°C	the plastics have not been melted	plug/Socket

3.5.3 ENVIRONMENT REQUIREMENTS					
DESCRIPTION	TEST CONDITION	REQUIREMENT			
3.5.3.1	IEC 60998-2-1, paragraph 12.1	No cracks visible.			
Heat Resistance	Subject specimens to 115±2°C for 168 hours and shall be	No material becomes sticky.			
	left alone for 1 to 2 hours in a room ambient for next examination/testing.	No material becomes greasy.  Specimen shall not undergo any change impairing their			
3.5.3.2	IEC 60998-2-1, paragraph 12.1	further use.			
Cold resistance	Subject specimens to -40±2°C for 168 hours and shall be	Tartifer dec.			
	left alone for 1 to 2 hours in a room ambient for next examination/testing				
3.5.3.3	IEC 60998-1, paragraph 12.2.				
Humidity	Subject specimens to 30±2°C, relative humidity 91%~95%				
	for 48 hours and shall be left alone for 1 to 2 hours in a				
	room ambient for next examination/testing				
3.5.3.4	EIA-364-26B, condition A				
Salt Spray	Salt concentration: 5%, temperature 32±2°C, 48hours.				

PDS: Rev: E
This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on the document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.

Form E-3005 Rev F

GS-12-625		Product Specification	FC	
TITLE			PAGE 5 of 8	REVISION D
Т	Terminal block- Pl	ug and Socket, Fixed Plug	AUTHORIZED BY  Jason Hsu	Nov. 11 <sup>th</sup> , 2009
			CLASSIFICATION Unrestri	cted

	Samples were measured after salt is removed by running water.	
3.5.3.5 Fire Test (Glow wire test)	Specimens with no visible flame and no sustained glowing; or flames and glowing on the specimen extinguished 30 seconds after the removal of the glow wire.	IEC 60695-2-10,-2-11,-2-12 Apply the glow-wire once for no longer than 5 seconds.

### 4.0 QUALITY ASSUREANCE PROVISIONS

# 4.1 **Equipment Calibration**

All test equipment and inspection facilities used in the performance of any test shall be maintained in a calibration system in accordance with QS9000.

### 4.2 <u>Inspection Conditions</u>

Unless otherwise specified, all inspections shall be performed under the following conditions:

a) Temperature: 25+/- 5°C

b) Relative Humidity: 30% to 60%

c) Barometric Pressure: Local ambient

### 4.3 Acceptance

- 4.3.1 Electrical and Mechanical requirements shall be as indicated in Paragraphs 3.5 using test data and appropriate statistical techniques.
- 4.3.2 Failures attributed to equipment, test setup or operator error shall not disqualify the product.

### 4.4 Qualification Testing

Qualification testing shall be performed on sample units predicted with equipment and procedures normally used in production. Test sequence are shown in Table 1(Pluggable plug), Table 2(pluggable socket), and Table3(Fixed plug).

PDS: Rev : E

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on the document may be used in any way or

Form E-3005 GS-01-001

GS-12-625		Product Specification	FC	
TITLE			PAGE 6 of 8	REVISION D
	Terminal block- P	lug and Socket, Fixed Plug	AUTHORIZED BY  Jason Hsu	Nov. 11 <sup>th</sup> , 2009
			CLASSIFICATION Unrestri	cted

TABLE 1: QUALIFICATION TESTING SEQUENCE for Pluggable Plug

		Test Group							
TEST	PARA	Α	В	С	D	Е	F	G	Н
					Test Se	equence			
Product examination	3.5.1.1	1	1	1	1	1	1	1	1
LLCR	3.5.1.2	2						3	
Insulation Resistance	3.5.1.3	3			3	3	3	4	
Dielectric withstanding	3.5.1.4	4		4	4	4	4		
voltage									
Mating/Un-mating force	3.5.2.1		2						
	3.5.2.2								
Torque	3.5.2.5		3						
Wire Pull Strength	3.5.2.4			2					
Temperature rise	3.5.1.5			3					
humidity test	3.5.3.3				2				
Heat resistance	3.5.3.1					2			
Cold resistance	3.5.3.2						2		
Salt Spray	3.5.3.4							2	
Fire Test	3.5.3.5								2
(Glow wire test)									
Qualification connector per group		3	3	3	3	3	3	3	3

TABLE 2: QUALIFICATION TESTING SEQUENCE-Pluggable Socket

				Test	Group							
TEST	PARA	Α	В	С	D	E	F	G	Н			
					Test Se	equence						
Product examination	3.5.1.1	1	1	1	1	1	1	1	1			
Insulation Resistance	3.5.1.3	2		3	3	3						
Dielectric withstanding voltage	3.5.1.4	3		4	4	4						
Pin Retention (Pull force)	3.5.2.6		2									
Humidity	3.5.3.3			2								
Heat resistance	3.5.3.1				2							
Cold resistance	3.5.3.2					2						
Salt Spray	3.5.3.4						2					
Fire Test	3.5.3.5							2				
(Glow wire test)												
Solder ability	3.5.2.7								2			

PDS: Rev: E

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on the document may be used in any way or

NUMBER GS-12-625	PE P	roduct Sp	ecification	1	FCJ			
TITLE					PAGE 7	of 8	REVISION	D
Terminal block- Plu	AUTHORIZED Jaso	<sub>BY</sub> on Hsu	Nov. 1	1 <sup>th</sup> , 2009				
						ON Unres	tricted	
Qualification connector per group	3	3	3	3	3	3	3	3

**TABLE 3: QUALIFICATION TESTING SEQUENCE-Fixed Plug** 

		Test Group								
TEST	PARA	Α	В	C	D	Е	F	G	Н	٦
					Tes	t Seque	nce			
Product examination	3.5.1.1	1	1	1	1	1	1	1	1	1
LLCR	3.5.1.2	2						3		
Insulation Resistance	3.5.1.3	3			3	3	3	4		
Dielectric withstanding voltage	3.5.1.4	4		4	4	4	4			
Torque	3.5.2.5		2							
Wire Pull Strength	3.5.2.4			2						
Temperature rise	3.5.1.5			3						
humidity test	3.5.3.3				2					
Heat resistance	3.5.3.1					2				
Cold resistance	3.5.3.2						2			
Salt Spray	3.5.3.4							2		
Solder ability	3.5.2.7								2	
Fire Test	3.5.3.5									2
(Glow wire test)										
Qualification connector per group		3	3	3	3	3	3	3	3	3

om E-3005 GS-01-001

GS-12-625	Product Specification	F	
TITLE		PAGE 8 of 8	REVISION D
Terminal	I block- Plug and Socket, Fixed Plug	AUTHORIZED BY  Jason Hsu	Nov. 11 <sup>th</sup> , 2009
		CLASSIFICATION Unrest	ricted

# **REVISION RECORD**

REV	PAGE	DESCRIPTION	ECR#	DATE
Α	All	Initial Release	DG09-0204	Nov 11 <sup>th</sup> , 2009
В	3	3.5.2.7 solderability test,	T09-1162	Dec 17 <sup>th</sup> , 2009
		Temperature change form 260 +/- 5 °C to 250 +/- 10°C		
С	All	Add phase-2 product series	T10-0079	Jun 15 <sup>th</sup> , 2010
D	2	Add p/n 20020336		Jan 31 <sup>th</sup> , 2010

Form E-3005 GS-01-001 Rev F

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

# FCI:

```
20020004-C081B01LF 20020004-D021B01LF 20020004-D031B01LF 20020004-D101B01LF 20020006-H031B01LF
 20020006-H061B01LF 20020008-C051B01LF 20020008-C081B01LF 20020008-G081B01LF 20020008-H021B01LF
 20020107-C021A01LF 20020107-C041A01LF 20020107-C061A01LF 20020107-C081A01LF 20020107-D021A01LF
 20020107-G041A01LF 20020107-G081A01LF 20020107-H021A01LF 20020107-H031A01LF 20020110-
C021A01LF 20020110-C061A01LF 20020110-C081A01LF 20020110-C141A01LF 20020110-D021A01LF 20020110-
D031A01LF 20020110-D041A01LF 20020110-D051A01LF 20020110-D071A01LF 20020110-D081A01LF 20020110-
G061A01LF 20020110-H021A01LF 20020110-H031A01LF 20020110-H041A01LF 20020110-H061A01LF 20020516-
M021B01LF 20020516-M041B01LF 20020000-C022B01LF 20020000-C105B01LF 20020004-C045B01LF
20020107-C022A01LF 20020107-C045A01LF 20020107-C105A01LF 20020111-C022A01LF 20020002-H022B01LF
20020111-H022A01LF 20020618-M021A01LF 20020618-M031A01LF 20020618-M041A01LF 20020618-M051A01LF
 20020618-M061A01LF 20020618-M071A01LF 20020618-M081A01LF 20020618-M091A01LF 20020618-
M101A01LF 20020618-M111A01LF 20020618-M121A01LF 20020618-M131A01LF 20020618-M141A01LF
20020618-M151A01LF 20020618-M161A01LF 20020620-M021A01LF 20020620-M031A01LF 20020620-M041A01LF
 20020620-M051A01LF 20020620-M061A01LF 20020620-M071A01LF 20020620-M081A01LF 20020620-
M091A01LF 20020620-M101A01LF 20020620-M111A01LF 20020620-M121A01LF 20020620-M131A01LF
20020620-M141A01LF 20020620-M151A01LF 20020620-M161A01LF 20020007-G021B01LF 20020007-G031B01LF
 20020007-G041B01LF 20020007-G061B01LF 20020007-G081B01LF 20020007-H021B01LF 20020007-
H031B01LF 20020007-H041B01LF 20020007-H061B01LF 20020007-H081B01LF 20020106-G021A01LF 20020106-
G031A01LF 20020106-G041A01LF 20020106-G061A01LF 20020106-G081A01LF 20020106-G101A01LF
20020106-H021A01LF 20020106-H031A01LF 20020106-H041A01LF 20020106-H061A01LF 20020106-H081A01LF
20020106-H101A01LF 20020007-G051B01LF 20020007-G071B01LF 20020007-G091B01LF
```