

## Linear Systems replaces discontinued Siliconix 2N4416A

### The 2N4416A is a N-Channel high frequency JFET amplifier

The 2N4416A N-channel JFET is designed to provide high-performance amplification at high frequencies.

The hermetically sealed TO-72 package is well suited for military applications. The TO-92 package provides a lower cost commercial option

#### 2N4416A Benefits:

- Wideband High Gain
- Very High System Sensitivity
- High Quality of Amplification
- High-Speed Switching Capability
- High Low-Level Signal Amplification

#### 2N4416A Applications:

- High-Frequency Amplifier / Mixer
- Oscillator
- Sample-and-Hold
- Very Low Capacitance Switches

#### FEATURES

DIRECT REPLACEMENT FOR SILICONIX 2N4416A

EXCEPTIONAL GAIN (400 MHz)	10dB (min)
VERY LOW NOISE FIGURE (400 MHz)	4dB (max)

VERY LOW DISTORTION  
HIGH AC/DC SWITCH OFF-ISOLATION

**ABSOLUTE MAXIMUM RATINGS**  
@ 25°C (unless otherwise noted)

#### Maximum Temperatures

Storage Temperature	-65°C to +200°C
Operating Junction Temperature	-55°C to +135°C

#### Maximum Power Dissipation

Continuous Power Dissipation	300mW
------------------------------	-------

#### MAXIMUM CURRENT

Gate Current (Note 1)	10mA
-----------------------	------

#### MAXIMUM VOLTAGES

Gate to Drain or Gate to Source	-35V
---------------------------------	------

#### 2N4416A ELECTRICAL CHARACTERISTICS @ 25°C (unless otherwise noted)

SYMBOL	CHARACTERISTIC	MIN	TYP.	MAX	UNITS	CONDITIONS
$BV_{GS}$	Gate to Source Breakdown Voltage	-35	--	--	V	$I_G = -1\mu A, V_{DS} = 0V$
$V_{GS(off)}$	Gate to Source Cutoff Voltage	-2.5	--	-6	V	$V_{DS} = 15V, I_D = 1nA$
$I_{DSS}$	Gate to Source Saturation Current	5	--	15	mA	$V_{DS} = 15V, V_{GS} = 0V$
$I_{GSS}$	Gate Leakage Current	--	--	-0.1	nA	$V_{GS} = -20V, V_{DS} = 0V$
$g_{fs}$	Forward Transconductance	4500	--	7500	$\mu S$	$V_{DS} = 15V, V_{GS} = 0V, f = 1kHz$
$g_{os}$	Output Conductance	--	--	50	$\mu S$	$V_{DS} = 15V, V_{GS} = 0V, f = 1MHz$
$C_{iss}$	Input Capacitance <sup>2</sup>	--	--	0.8	pF	
$C_{rss}$	Reverse Transfer Capacitance <sup>2</sup>	--	--	4	pF	
$C_{oss}$	Output Capacitance <sup>2</sup>	--	--	2	pF	
$e_n$	Equivalent Input Noise Voltage	--	6	--	nV/√Hz	$V_{DS} = 10V, V_{GS} = 0V, f = 1kHz$

#### 2N4416A HIGH FREQUENCY ELECTRICAL CHARACTERISTICS @ 25°C (unless otherwise noted)

SYMBOL	CHARACTERISTIC	100 Mhz		400 Mhz		UNITS	CONDITIONS
		MIN	MAX	MIN	MAX		
$g_{iss}$	Input Conductance	--	100	--	1000	$\mu S$	$V_{DS} = 15V, V_{GS} = 0V$
$b_{iss}$	Input Susceptance <sup>2</sup>	--	2500	--	10000		
$g_{oss}$	Output Conductance	--	75	--	100		
$b_{oss}$	Output Susceptance <sup>2</sup>	--	1000	--	4000		
$G_{fs}$	Forward Transconductance	--	--	4000	--	dB	$V_{DS} = 15V, I_D = 5mA$
$G_{ps}$	Power Gain <sup>2</sup>	18	--	10	--		
NF	Noise Figure <sup>2</sup>	--	2	--	4		

- NOTES**
- Absolute maximum ratings are limiting values above which 2N4416A serviceability may be impaired.
  - Not production tested, guaranteed by design

Micross Components Europe



Available Packages:

TO-72 (Bottom View)

TO-92 (Bottom View)



2N4416A in TO-72  
2N4416A in TO-92  
2N4416A in bare die.



Tel: +44 1603 788967

Email: [chipcomponents@micross.com](mailto:chipcomponents@micross.com)

Web: <http://www.micross.com/distribution>

Please contact Micross for full package and die dimensions

Information furnished by Linear Integrated Systems and Micross Components is believed to be accurate and reliable. However, no responsibility is assumed for its use; nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Linear Integrated Systems.