

DEVICE TYPE	MIL-S-19500/	V _{CB0} VOLTS	V _{CEO} VOLTS	I _C (CONT.) AMPS	POWER (@T _C = 25°C) WATTS	CASE TYPE	CHIP TYPE
2N2880 JAN, TX, TXV	315	110	80	5.0	30*	TO-111	184
2N3418 JAN, TX, TXV	393	85	60	5.0	15*	TO-5/39	185
2N3419 JAN, TX, TXV	393	125	80	5.0	15*	TO-5/39	185
2N3420 JAN, TX, TXV	393	85	60	5.0	15*	TO-5/39	185
2N3421 JAN, TX, TXV	393	125	80	5.0	15*	TO-5/39	185
2N3439 JAN, TX, TXV	368	450	350	1.0	5	TO-5/39	100
2N3440 JAN, TX, TXV	368	300	250	1.0	5	TO-5/39	100
2N3740 JAN, TX, TXV	441	-60	-60	-4.0	25	TO-66	269
2N3741 JAN, TX, TXV	441	-80	-80	-4.0	25	TO-66	269
2N3749 JAN, TX, TXV	315	110	80	5.0	30*	TO-111/I	184
2N3846 JAN, TX	412	300	200	20.0	150*	TO-63	114
2N3847 JAN, TX	412	400	300	20.0	150*	TO-63	114
2N3902 JAN, TX	371	700	400	3.5	100**	TO-3	142
2N3996 JAN, TX, TXV	374	100	80	5.0	30*	TO-111/I	184
2N3997 JAN, TX, TXV	374	100	80	5.0	30*	TO-111/I	184
2N3998 JAN, TX, TXV	374	100	80	5.0	30*	TO-111	184
2N3999 JAN, TX, TXV	374	100	80	5.0	30*	TO-111	184
2N4150 JAN, TX, TXV	394	100	70	10.0	5*	TO-5	185
2N4865 JAN, TX, TXV	380	100	80	50.0	350	TO-114	196
2N5157 JAN, TX	371	700	500	3.5	100**	TO-3	142
2N5237 JAN, TX, TXV	394	150	120	10.0	5*	TO-5	185
2N5238 JAN, TX, TXV	394	200	170	10.0	5*	TO-5	185
2N5250 JAN, TX, TXV	380	125	100	50.0	350	TO-114	196
2N5251 JAN, TX, TXV	380	180	150	50.0	350	TO-114	196
2N5415 JAN, TX, TXV	485	-200	-200	-1.0	10	TO-5/39	200
2N5416 JAN, TX, TXV	485	-350	-300	-1.0	10	TO-5/39	200
2N5664 JAN, TX, TXV	455	250	200	5.0	30*	TO-66	140
2N5665 JAN, TX, TXV	455	400	300	5.0	30*	TO-66	140
2N5666 JAN, TX, TXV	455	250	200	5.0	15*	TO-5	140
2N5667 JAN, TX, TXV	455	400	300	5.0	15*	TO-5	140
2N6306 JAN, TX, TXV	498	500	250	8.0	125	TO-3	104
2N6308 JAN, TX, TXV	498	700	350	8.0	125	TO-3	104
2N6546 JAN, TX, TXV	525	850	450	15.0	175	TO-3	105
2N6547 JAN, TX, TXV	525	650	350	15.0	175	TO-3	105

*T_C = 100°C in lieu of 25°C

**T_C = 75°C in lieu of 25°C