

Advanced Small Signal MOSFET 2N7000BU/2N7000TA

FEATURES


- Fast Switching Times
- Improved Inductive Ruggedness
- Lower Input Capacitance
- Extended Safe Operating Area
- Improved High Temperature Reliability

$$BV_{DSS} = 60 \text{ V}$$

$$R_{DS(on)} = 5.0 \ \Omega$$

$$I_D = 200 \text{ mA}$$

TO-92



1.Source 2. Gate 3. Drain

Absolute Maximum Ratings

Symbol	Characteristic	Value	Units
V_{DSS}	Drain-to-Source Voltage	60	V
I_D	Continuous Drain Current ($T_C=25^\circ\text{C}$)	200	mA
	Continuous Drain Current ($T_C=100^\circ\text{C}$)	110	
I_{DM}	Drain Current-Pulsed ^①	1000	mA
V_{GS}	Gate-to-Source Voltage	± 30	V
P_D	Total Power Dissipation ($T_C=25^\circ\text{C}$)	400	mW
	Linear Derating Factor	3.2	mW/ $^\circ\text{C}$
T_J, T_{STG}	Operating Junction and Storage Temperature Range	-55 to +150	$^\circ\text{C}$
T_L	Maximum Lead Temp. for Soldering Purposes, 1/8" from case for 5-seconds	300	

Thermal Resistance

Symbol	Characteristic	Typ.	Max.	Units
$R_{\theta JA}$	Junction-to-Ambient	--	312.5	$^\circ\text{C}/\text{W}$

Electrical Characteristics ($T_C=25^\circ\text{C}$ unless otherwise specified)

Symbol	Characteristic	Min.	Typ.	Max.	Units	Test Condition
BV_{DSS}	Drain-Source Breakdown Voltage	60	--	--	V	$V_{GS}=0V, I_D=250\mu A$
$V_{GS(th)}$	Gate Threshold Voltage	0.3	--	3.9	V	$V_{DS}=V_{GS}, I_D=250\mu A$
		0.4	--	2.2		$V_{DS}=V_{GS}, I_D=1mA$
I_{GSS}	Gate-Source Leakage, Forward	--	--	100	nA	$V_{GS}=15V$
	Gate-Source Leakage, Reverse	--	--	-100		$V_{GS}=-15V$
I_{DSS}	Drain-to-Source Leakage Current	--	--	250	μA	$V_{DS}=60V$
		--	--	1000		$V_{DS}=45V, T_C=125^\circ\text{C}$
$R_{DS(on)}$	Static Drain-Source On-State Resistance ^②	--	--	5.0	Ω	$V_{GS}=10V, I_D=0.5A$
g_{fs}	Forward Transconductance ^②	0.1	0.3	--	S	$V_{DS}=15V, I_D=0.5A$
C_{iss}	Input Capacitance	--	30	--	pF	$V_{GS}=0V, V_{DS}=25V,$ $f=1MHz$
C_{oss}	Output Capacitance	--	12	--		
C_{rss}	Reverse Transfer Capacitance	--	3.0	--		
$t_{d(on)}$	Turn-On Delay Time	--	--	10	ns	$V_{DD}=30V, I_D=0.5A,$ $R_G=15\Omega$ ^{② ③}
t_r	Rise Time	--	--	10		
$t_{d(off)}$	Turn-Off Delay Time	--	--	10		
t_f	Fall Time	--	--	10		

Notes ;

- ① Repetitive Rating : Pulse Width Limited by Maximum Junction Temperature
- ② Pulse Test : Pulse Width = 250 μs , Duty Cycle $\leq 2\%$
- ③ Essentially Independent of Operating Temperature

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACE _x [™]	FAST [®]	MICROWIRE [™]	SILENT SWITCHER [®]	UHC [™]
Bottomless [™]	FAST _r [™]	OPTOLOGIC [®]	SMART START [™]	UltraFET [®]
CoolFET [™]	FRFET [™]	OPTOPLANAR [™]	SPM [™]	VCX [™]
CROSSVOLT [™]	GlobalOptoisolator [™]	PACMAN [™]	STAR*POWER [™]	
DenseTrench [™]	GTO [™]	POP [™]	Stealth [™]	
DOME [™]	HiSeC [™]	Power247 [™]	SuperSOT [™] -3	
EcoSPARK [™]	I ² C [™]	PowerTrench [®]	SuperSOT [™] -6	
E ² CMOS [™]	ISOPLANAR [™]	QFET [™]	SuperSOT [™] -8	
EnSigna [™]	LittleFET [™]	QS [™]	SyncFET [™]	
FACT [™]	MicroFET [™]	QT Optoelectronics [™]	TinyLogic [™]	
FACT Quiet Series [™]	MicroPak [™]	Quiet Series [™]	TruTranslation [™]	

STAR*POWER is used under license

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.