

1N/FDLL 456/A - 1N/FDLL 459/A



DO-35



LL-34

THE PLACEMENT OF THE EXPANSION GAP HAS NO RELATIONSHIP TO THE LOCATION OF THE CATHODE TERMINAL

COLOR BAND MARKING

DEVICE	1ST BAND	2ND BAND
FDLL456	BROWN	WHITE
FDLL456A	BROWN	WHITE
FDLL457	RED	BLACK
FDLL457A	RED	BLACK
FDLL458	RED	BROWN
FDLL458A	RED	BROWN
FDLL459	RED	RED
FDLL459A	RED	RED

High Conductance Low Leakage Diode

Sourced from Process 1M. See MMBD1501/A-1505/A for characteristics.

Absolute Maximum Ratings*

TA = 25°C unless otherwise noted

Symbol	Parameter	Value	Units	
W _{IV}	Working Inverse Voltage	456/A	25	V
		457/A	60	V
		458/A	125	V
		459/A	175	V
I _O	Average Rectified Current	200	mA	
I _F	DC Forward Current	500	mA	
i _f	Recurrent Peak Forward Current	600	mA	
i _{f(surge)}	Peak Forward Surge Current Pulse width = 1.0 second Pulse width = 1.0 microsecond	1.0	A	
		4.0	A	
T _{stg}	Storage Temperature Range	-65 to +200	°C	
T _J	Operating Junction Temperature	175	°C	

*These ratings are limiting values above which the serviceability of any semiconductor device may be impaired.

NOTES:

- 1) These ratings are based on a maximum junction temperature of 200 degrees C.
- 2) These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.

Thermal Characteristics

TA = 25°C unless otherwise noted

Symbol	Characteristic	Max	Units
		1N / FDLL 456/A - 459/A	
P _D	Total Device Dissipation Derate above 25°C	500	mW
		3.33	mW/°C
R _{θJA}	Thermal Resistance, Junction to Ambient	300	°C/W

High Conductance Low Leakage Diode

(continued)

Electrical Characteristics

TA = 25°C unless otherwise noted

Symbol	Parameter	Test Conditions	Min	Max	Units
BV	Breakdown Voltage	456/A	IR = 100 μA	30	V
		457/A	IR = 100 μA	70	V
		458/A	IR = 100 μA	150	V
		459/A	IR = 100 μA	200	V
IR	Reverse Current	456/A	VR = 25 V		25 nA
			VR = 25 V, TA = 150°C		5.0 μA
		457/A	VR = 60 V		25 nA
			VR = 60 V, TA = 150°C		5.0 μA
		458/A	VR = 125 V		25 nA
	VR = 125 V, TA = 150°C		5.0 μA		
	459/A	VR = 175 V		25 nA	
		VR = 175 V, TA = 150°C		5.0 μA	
VF	Forward Voltage	456	IF = 40 mA		1.0 V
		457	IF = 10 mA		1.0 V
		458	IF = 7.0 mA		1.0 V
		459	IF = 3.0 mA		1.0 V
		456/A-459/A	IF = 100 mA		1.0 V
CO	Diode Capacitance	VR = 0, f = 1.0 MHz		6.0	pF

1N/FD/LL 456/A / 457/A / 458/A / 459/A

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACEx™	HiSeC™	SuperSOT™-8
Bottomless™	ISOPANAR™	SyncFET™
CoolFET™	MICROWIRE™	TinyLogic™
CROSSVOLT™	POP™	UHC™
E ² CMOS™	PowerTrench®	VCX™
FACT™	QFET™	
FACT Quiet Series™	QS™	
FAST®	Quiet Series™	
FASTr™	SuperSOT™-3	
GTO™	SuperSOT™-6	

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.